



Topology optimization for transient heat transfer problems

Zeidan, Said; Sigmund, Ole; Lazarov, Boyan Stefanov

Publication date:
2016

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Zeidan, S., Sigmund, O., & Lazarov, B. S. (2016). *Topology optimization for transient heat transfer problems*. Abstract from ECCOMAS Congress 2016, Hersonissos, Greece.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Topology optimization for transient heat transfer problems

Said Zeidan *, Ole Sigmund, Boyan S. Lazarov

Technical University of Denmark
Department of Mechanical Engineering
Nils Koppels Allé, 2800 Lyngby, Denmark
szeidan@mek.dtu.dk

ABSTRACT

The focus of this work is on passive control of transient heat transfer problems using the topology optimization (TopOpt) method [1]. The goal is to find distributions of a limited amount of phase change material (PCM), within a given design domain, which optimizes the heat energy storage [2]. Our aim is to obtain manufacturable designs [3] as well as demonstrating TopOpt for mixed multiphysics problems [4]. TopOpt provides material distributions in a given design domain, optimized with respect to a given objective and satisfying a set of constraints. Originating in static mechanical problems, TopOpt has later been extended to transient problems in mechanics and photonics (e.g. [5], [6] and [7]). In the presented approach, the optimization is gradient-based, where in each iteration the non-steady heat conduction equation is solved, using the finite element method and an appropriate time-stepping scheme.

A PCM can efficiently absorb heat while keeping its temperature nearly unchanged [8]. The use of PCM in e.g. electronics [9] and mechanics [10], yields improved performance and lower costs depending on a.o., the spatial distribution of PCM.

The considered problem consists in optimizing the distribution of PCM in a design domain, subject to a periodic heat influx. The objective is to stabilize the heat outflow. Application examples include keeping constant room temperature for oscillatory heat input or keeping constant working temperature of a CPU subjected to time varying computational load.

References

- [1] M. P. Bendsøe and O. Sigmund, *Topology Optimization - Theory, Methods, and Applications*. Springer Verlag, 2003.
- [2] V. Srinivas and G. Ananthasuresh, "Analysis and topology optimization of heat sinks with a phase- change material on comsol multiphysicsTM platform", *Proceedings of the COMSOL Users Conference*, 2006.
- [3] M. Schevenels, B. S. Lazarov, and O. Sigmund, "Robust topology optimization accounting for spatially varying manufacturing errors", *Computer Methods in Applied Mechanics and Engineering*, vol. 200, no. 49-52, pp. 3613-3627, 2011.
- [4] S. Madsen, N. P. Lange, L. Giuliani, G. Jomaas, B. S. Lazarov, and O. Sigmund, "Topology optimization for simplified structural fire safety: an alternative way of imposing length scale", "submitted," 2015.
- [5] Y. Elesin, B. S. Lazarov, J. S. Jensen, and O. Sigmund, "Design of robust and efficient photonic switches using topology optimization", *Photonics and Nanostructures - Fundamentals and Applications*, vol. 10, no. 1, pp. 153-165, 2012.
- [6] J. Dahl, J. S. Jensen, and O. Sigmund, "Topology optimization for transient problems in one dimension: Design of lters and pulse modulators", *Structural and Multidisciplinary Optimization*, vol. 36, pp. 585-595, 2008.
- [7] R. Matzen, J. Jensen, and O. Sigmund, "Topology optimization for transient response of photonic crystal structures", *Journal of the Optical Society of America B*, vol. 27, no. 10, pp. 2040- 2050, 2010.
- [8] A. S. Fleischer, *Thermal energy storage using phase change materials : fundamentals and applications*. 2015.
- [9] F. Kaplan, C. De Vivero, S. Howes, M. Arora, H. Homayoun, W. Burleson, D. Tullsen, and A. K. Coskun, "Modeling and analysis of phase change materials for efficient thermal management", *2014 32nd IEEE International Conference on Computer Design, Icccd 2014, IEEE Int. Conf. Comput. Des., Icccd*, pp. 6974690, 256-263, 2014.
- [10] A. Stockwell, N. Neithalath, and S. Rajan, "Multiphysics design optimization model for structural walls incorporating phase-change materials", *Engineering Optimization*, vol. 47, no. 3, pp. 308-327, 2015.